

Oak Alamo Vivo

Article number	10036667 / EAG8VKFD	Surface structure	unbrushed	Moisture content	5-9%
Wood	Oak	Bevel	beveled 2V	Density	>= 500kg/m³
Grading	Vivo	Number of slotted top layers	2	Fire protection classification	
Product type	3-layer parquet	Appearance	Brown floors	Content of formaldehyde	E 1
Product group	14 mm Plank 14mm Plank 138	Style	Rustic	PCP content	NPD
Format	Plank 14mm Plank 138	m² per carton	3,04	Brinell Value	38
Dimensions	14 x 138 x 2200 mm	Boards per carton	10	Breaking strength	NPD
Top layer thickness	3,5 mm	Weight per carton (kg)	23,5	Thermal conductivity	
Core material	Spruce / Spruce	m² per pallet	127,68	Thermal resistance value	
Connection	5G Click	Boxes per pallet	42	Performance classification	Class 1
Floor heating	suitable	Weight per pallet (kg)	987	Antislip performance	USRV 59
Treatment	Live Natural oil	EN Norm	EN 13489	Nobb.number	45955874
Colour	Alamo	FSC claim	controlled sources	EAN Code	7035580081487











The mark of responsible forestry

Wood is a product of nature - each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

